

FIREWORLD DRY POWDER ABE FIRE EXTINGUISHERS

Certified & Approved to AS/NZS 1841.5



Fireworld Fire Extinguisher Features:

- Deep drawn steel cylinder with welded base and robust skirt.
- Powder coated with UV resistant paint finish, giving extra resistance to standard corrosive environments together with dents and wears associated with normal fire extinguisher use.
- EPDM type UV resistant discharge hose with dust cap.
- Zinc plated brass valve with pressure indicator.
- 316 Stainless steel handles and levers – suitable for aggressive environments.
- Non-Aluminium Hose Ferrules on 4.5kg & 9.0kg required for underground use.
- 316 Stainless steel hose retaining clip and bands on 2.5kg, 4.5kg & 9.0kg models
- Sturdy solid stainless steel hanging bracket, ideal for aggressive environments.
- A rugged epoxy coated metal vehicle bracket comes with 1.0kg, 2.0kg & 2.5kg models. 2.5kg model comes with wall bracket for internal installation.
- Aluminium inspection tag and ring (to be removed for underground coal mines).
- Fire extinguishers have been fire tested for the use in A, B & E Class fires.

- All fire extinguishers should be serviced to the relevant, current Australian Standard. *AS1851 - Maintenance of Fire Protection Systems and Equipment.*

Fireworld ABE fire extinguisher is suitable for the following Applications:

- A Class Fires (paper, wood, textiles)
- B Class Fires (flammable liquid fires such as oils, paints and solvents)
- E Class Fires (energised electrical fires such as switchboards and electrical motors)



PRODUCT CODE	CAPACITY	FIRE RATING	AGENT	OPERATING PRESSURE	DISCHARGE TIME (approx)	DIMENSIONS (height x outside diameter in mm)	OVERALL MASS (approx)
PABE10	1.0kg	2A10B:E	20%MAP	1500kpa	8-11sec	340mm x 95mm	1.9kg
PABE15	1.5kg	3A10B:E	20% MAP	1500kpa	8 – 11sec	390mm x 110mm	3.0kg
PABE20	2.0kg	3A30B:E	20%MAP	1500kpa	11-14sec	400mm x 120mm	3.7kg
PABE25	2.5kg	4A40B:E	70%MAP	1500kpa	13-16sec	440mm x 135mm	4.6kg
PABE45	4.5kg	6A60B:E	70%MAP	1500kpa	17-20sec	510mm x 150mm	7.5kg
PABE90	9.0kg	10A80B:E	70%MAP	1500kpa	20-23ec	590mm x 195mm	13.6kg