

## FIREWORLD CARBON DIOXIDE (CO2) FIRE EXTINGUISHER

Certified & Approved to AS/NZS 1841.6



### Fire Extinguisher Features:

- Lightweight Aluminium Cylinder. AS2030.1
- Powder coated with UV resistant paint finish.
- High pressure hose assembly with the Bell Horn design.
- 316 Stainless steel handles and levers – suitable for aggressive environments.
- CO2 is a clean nontoxic gas ideal for office areas with computers or sensitive electronics.
- Sturdy solid stainless steel hanging bracket.
- Fire extinguishers have been fire tested for the use in B & E Class fires. Rating is an indication of the level of fire testing achieved. All testing is carried out by fire professionals.
- All fire extinguishers should be serviced to the relevant, current Australian Standard. *AS1851 - Maintenance of Fire Protection Systems and Equipment*

### FIREWORLD CO2 fire extinguisher is suitable for the following Applications:

- B Class Fires (flammable liquid fires such as oils, paints and solvents)
- E Class Fires (energised electrical fires such as switchboards and electrical motors)



PRODUCT CODE	CAPACITY	FIRE RATING	AGENT	DISCHARGE TIME (approx)	DIMENSIONS (height x outside diameter in mm)	OVERALL MASS (approx)
PCD20	2.0kg	5B:E	CO2	8 sec	555mm x 158mm	5.0kg
PCD35	3.5kg	10B:E	CO2	10.5sec	590mm x 150mm	8.9kg
PCD50	5.0kg	10B:E	CO2	11.sec	675mm x 160mm	11.9kg