

FIREWORLD AIR FOAM FIRE EXTINGUISHER

Certified & Approved to AS/NZS 1841.4



Fire Extinguisher Features:

- Stainless steel cylinder
- Filled and charged ready to use
- Powder coated with UV resistant paint finish
- Stainless steel handles and levers – suitable for aggressive environments
- Heavy duty zinc plated brass valve with easy to read pressure indicator
- Wall hanging bracket
- Australian Standards Aluminium Inspection Tag supplied and fitted to extinguisher
- Schrader valve, 45 degrees from horizontal for easier recharging
- Presto AFFF Foam is a fluorine free, Environmentally friendly foam
- Fire extinguishers have been fire tested for the use in A Class fires. Rating is an indication of the level of fire testing achieved. All testing is carried out by fire professionals.
- All fire extinguishers should be serviced to the relevant, current Australian Standard. *AS1851 - Maintenance of Fire Protection Systems and Equipment*

Fireworld Foam fire extinguisher is suitable for the following Applications:

- A Class Fires (paper, wood, textiles)
- B Class Fires (flammable liquid fires such as oils, paints and solvents)
- Do not use on E Class fires



Water and AFFF fire extinguisher

PRODUCT CODE	CAPACITY	FIRE RATING	AGENT	DISCHARGE TIME (approx)	DIMENSIONS (height x outside diameter in mm)	OVERALL MASS (approx)
PAF	9.0Lt	3A:30B	Presto Foam	TBA	610mm x 193mm	12.5kg

Available from

