

**3 AAA** (included)

**LXPP-5452G**

## NIGHTSTICK DUAL-FUNCTION HEADLAMP




Includes a heavy-duty rubber, and a nylon head strap **for use on a hard hat.**



**Single Body Switch.** High-brightness Spotlight, Low-brightness Spotlight



**ANSI IP-67 Dustproof / Waterproof** with a 2 meter drop rating.



**Adjustable ratchet tilt head** made from an engineered polymer housing

**ATEX**

**ZONE 0**

**IECEx**

**CLASS I  
DIV 1**

**IP-X7**

**WATER  
PROOF**

**CERTIFIED**



**180 LUMENS**

## PRODUCT SPECIFICATION SHEET

### ITEM NUMBER/UPC

- LXPP-5452G, UPC 0 1739880301 4

### MARKET APPLICATIONS

- Hazardous work environments, industrial, automotive, law enforcement, fire & rescue

### CERTIFICATIONS

- cETLus, CE, ATEX, IECEx

### CASE MATERIAL

- Engineered Polymer

### SPOTLIGHT LUMENS/RUNTIME

- HIGH: 180L, 6 hrs. runtime  
- LOW: 90L, 19 hrs. runtime

### CANDELA

- HIGH: 2,180  
- LOW: 962

### BEAM DISTANCE

- HIGH: 93m  
- LOW: 62m

### DUST/WATER RATING

ANSI IP-67 Dustproof / Waterproof

### DROP RATING

- 2 meters

### DIMENSIONS

- LENGTH: 2.4 in (61 mm)  
- WIDTH: 1.9 in (48 mm)  
- DEPTH: 1.8 in (46 mm)  
- WEIGHT: 3.5 oz (99 g)

### BATTERY


















- 3 AAA (Included)

### WARRANTY

- Limited lifetime warranty

### WHAT'S INCLUDED

- Headlamp  
- 3 AAA batteries  
- Elastic non-slip headband  
- Rubber hardhat strap  
- Instruction manual

FL 1 STANDARD	HIGH	LOW		
	<b>180</b> LUMENS	<b>90</b> LUMENS		
	<b>6h</b>	<b>19h</b>		
	<b>93m</b>	<b>62m</b>		
	<b>2180cd</b>	<b>962cd</b>		
				
				
<div></div> <div><b>Model LXPR-5452G</b> CLASS I DIV 1 GRPS A-D T4 CLASS II &amp; III GRPS E-G T135C CLASS I ZONE 0 AEx ia IIC T4 Ga CLASS I ZONE 0 Ex ia IIC T4 Ga Ex ia op is IIC T4 Ga Intertek ITS 13 ATEX27854X ITS21UKEX0247X IECEx ITS 17.0002X -20°C ≤ Tamb ≤ +40°C 1.5V/Cell AAAAlkaline MFG MM-YY</div>				
<div>SEE INSTRUCTION MANUAL VOIR MANUEL</div> <div><b>CERTIFIED</b> </div>				

Available from

