

3 AA BATTERIES

XPP-5422GXA

DUAL-LIGHT

285-lumen Dual-Light provides simultaneous **flashlight and floodlight** operation


IP-67
DUST/WATER
PROOF

ZONE 0

CLASS I
DIV 1



Simultaneous **flashlight and floodlight** operation



Sharp focused flashlight beam



Durable polymer body is **impact & chemical resistant**



Large, textured buttons



285 LUMENS

PRODUCT SPECIFICATION SHEET

ITEM NUMBER/UPC

- LXPP-5422GXA, UPC 0 1739880811 8

MARKET APPLICATIONS

- Hazardous work environments, industrial, fire & rescue

CERTIFICATIONS

- cETLus, ATEX, IECEx, CE, InMetro, UKCA

CASE MATERIAL

- Engineered polymer

LUMENS/RUNTIME

FLASHLIGHT

- 210L, 14 hrs. runtime

FLOODLIGHT

- 130L, 20 hrs. runtime

DUAL-LIGHT

- 285L, 10 hrs. runtime

CANDELA

- 7,970

BEAM DISTANCE

- 187 m

WATER RATING

- ANSI IP-67 dustproof / waterproof

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 7.0 in (178 mm)

- HANDLE DIAMETER: 1.1 in x 1.5 in (28 mm x 38 mm)

- HEAD DIAMETER: 1.8 in (46 mm)

- WEIGHT: 6.9 oz (196 g)

POWER SOURCE

- AA batteries (not included)

WARRANTY

- Limited lifetime

WHAT'S INCLUDED

- Flashlight
- Removable lanyard
- Instruction manual

FL 1 STANDARD	SPOT	FLOOD	DUAL-LIGHT
	210 LUMENS	130 LUMENS	285 LUMENS
	14h	20h	10h
	187m		
	7970cd		



Intertek



21-AV4BO-0137X

Model LXPP-5422GXA

ID 4003544

INTRINSICALLY SAFE
SECURITE INTRINSEQUE

CLASS I DIV 1 GRPS A-D T3
CLASS II & III DIV 1 GRPS E-G T135C
CLASS I ZONE 0 AEx ia IIC T3 Ga
CLASS I ZONE 0 Ex ia IIC T3 Ga
Ⓜ I M 1 Ex ia op is I Ma
Ⓜ II 1 G Ex ia op is IIC T3 Ga

Ex ia op is I Ma
Ex ia op is IIC T3 Ga
Intertek ITS 13 ATEX27837X
IECEx ITS 16.0067X
UKEX: ITS21UKEX0264X
-20°C ≤ Tamb ≤ +40°C
1.5V/Cell AA Alkaline

Conforms to:

ANSI/UL STD 913, ANSI/UL
60079-0, ANSI/UL 60079-11
ANSI/ISA 60079-26

Certified to:

CAN/CSA STD C22.2 No 157
CAN/CSA STD C22.2 No 60079-0
CAN/CSA STD C22.2 No 60079-11
CSA STD C22.2 No 25

SEE INSTRUCTION MANUAL
VOIR MANUEL

MFG MM-YY

CERTIFIED



Available from

