

RECHARGEABLE

LXPR-5568GX

NIGHTSTICK INTRANT® IS RECHARGEABLE DUAL-LIGHT ANGLE LIGHT



HEAD ROTATES 90°

45°

EXCLUSIVE
DOWNWARD FLOODLIGHT

IP-67
DUST/WATER
PROOF

ZONE 0


GRAB-N-GO
CHARGING BASE



Head rotates 90° – directing beam exactly where it's needed most



45° downward floodlight lights an 8 foot walking area



Easy-to-use with gloves, the large switches **independently control** separate LEDs



Heavy-duty, clip and V-ring **securely holds tight to gear** in any situation



205 LUMENS

PRODUCT SPECIFICATION SHEET

ITEM NUMBER/UPC

XPR-5568GX (Green), 0 17398 80630 5

CERTIFICATIONS

- CE, cULus, ATEX, IECEx, InMetro, UKCA
- Meets requirements of NFPA

PATENTS

- 9,713,217 10,119,663

CASE MATERIAL

- Engineered polymer

LUMENS/RUNTIME

FLASHLIGHT

- HIGH: 200L, 7 hrs. runtime
- MEDIUM: 110L, 15 hrs. runtime
- LOW: 60L, 27 hrs. runtime
- STROBE

FLOODLIGHT

- HIGH: 100L, 7 hrs. runtime
- MEDIUM: 40L, 15 hrs. runtime
- SURVIVAL: 20L, 27 hrs. runtime

DUAL-LIGHT

- 205L, 7 hrs. runtime

CANDELA

FLASHLIGHT

- HIGH: 40,256
- MEDIUM: 15,625
- LOW: 8,750

BEAM DISTANCE

FLASHLIGHT

- HIGH: 401m
- MEDIUM: 250m
- LOW: 187m

WATER RATING

- IP-67 (dustproof and waterproof)

DROP RATING

- 2 meters

DIMENSIONS

- LENGTH: 6.6 in (168mm)
- WIDTH: 2.6 in (66mm)
- DEPTH: 2.6 in (66mm)
- HEAD DIAMETER: 2.1 in (53mm)
- WEIGHT: 10.6 oz (301g)(with batteries)

BATTERY







- Rechargeable Li-ion battery pack
- AA Battery carrier (batteries not included)

WARRANTY

- Limited lifetime warranty

WHAT'S INCLUDED

- Angle light
- Rechargeable Li-ion battery pack
- AA battery carrier
- Snap-in rapid charger (Charge Input: 24VDC max) Meets requirements of NFPA
- AC & DC power supplies
- Instruction manual

FL 1 STANDARD	SPOT HIGH	SPOT LOW	DUAL-LIGHT
	200 LUMENS	60 LUMENS	205 LUMENS
	7h	27h	7h
	401m		
	40256cd		
			
			

Model LXPR-5568GX
 Ex II FL ASHLIGHT FOR USE IN HAZARDOUS LOCATIONS

For use with Design 1 Li-ion Battery Pack (3000mAh) or 1 (5500mAh) with 3 AA Emergency Type (900) or 1 (900) batteries only.

CLASS I DIV 1 GRPS A-D T4
 CLASS II & III DIV 1 GRPS E-G T4 T5 T6
 CLASS I ZONE 0 AEx ia IIC T4 Gb

Ex ia op ex I Ma
 Ex ia op ex I Mb
 Ex ia op ex IIC T4 Gb
 Ex ia op ex IIC T4 Gb

US Patents 9,713,217 & 10,119,663

CE 2575
 UK CA 0359
 Meets the requirements of NFPA-1971-8.6 (2013)

IECEx 17 ATEX 1927
 US220932X20A
 IECEx UL 17 0002
 -20°C to Tamb to +40°C
 1.5V/Cell Alkaline
 3.7V/Cell Li-ion
 3000mAh
 10h 10V

Control Drawing: 1.5508-CERT-DWG1-03
 For Battery Charger Connection see Instruction Manual Drawing: 1.5562-08-MECH-DWG1-09

SEE INSTRUCTION MANUAL
 VOIR MANUEL

MFG MM-YY

CERTIFIED									
CE	cULus LISTED	EX	IECEx	NFPA	UK CA 0359	INMETRO	BC	PS 18046	KS

Available from

