

# Confined Space Gas Detector Kit

## Honeywell BW™ MicroClip X3



safetyquip.com.au

REAL TIME GAS READINGS AT A GLANCE



## Honeywell

Our Honeywell 4-Gas Confined Space Gas Detector Kit is a popular choice for many confined space applications. Often used in the civil works, mining and water utility industries, the kit is supplied in a robust water and dust proof carry case with a Honeywell BW™ MicroClip X3 4-Gas Detector.



### ■ Sensors fitted are:

Combustible Gas (LEL), Oxygen (O<sub>2</sub>), Hydrogen Sulphide (H<sub>2</sub>S), Carbon Monoxide (CO)



### ■ Kit contains:

- 1. Nanuk 910 Case with Custom Foam Insert**  
Rugged and compact protective hard case. Waterproof and shock resistant.
- 2. Gas Detector**  
Honeywell BW™ MicroClip X3 Gas Detector
- 3. Wall Charger**  
For recharging of gas detector battery
- 4. Manual Pump/Tubing**  
For use testing the air before entering the confined space
- 5. Cylinder of Bump Test Gas**  
Quad-gas mix
- 6. Bump Test Cap**  
Connects detector to gas cylinder regulator
- 7. Regulator**  
0.5L Trigger Style



### ■ SafetyQuip product information:

<b>Product Code</b>	RGMKSQMCX3Y
<b>Description</b>	Confined Space Kit with Honeywell BW™ MicroClip X3 4-Gas Detector
<b>UOM</b>	Each

Ask your SafetyQuip branch for a demonstration of the Honeywell Gas Detector Kit

SAFETY GEAR ■ WORKWEAR  
FOOTWEAR ■ SITE SAFETY

# Honeywell BW™ MicroClip X3

## 4-Gas Detector

safetyquip.com.au



RELIABLE - ACCURATE - EASY TO USE

## Honeywell

### ■ Features and Benefits

- Simultaneously monitor for up to 4 gases including O<sub>2</sub>, H<sub>2</sub>S, CO and combustibles
- Popular for confined space work
- IP68 rating
- Compact, lightweight and easy to use with one-button operation
- Flashing green IntelliFlash™ light for compliance at a glance
- Guaranteed to run an entire shift, even at -20 °C
- Servicable with 5 year expected run time
- Honeywell Safety Suite Device management
- Extended reliability with 3-year warranty



### ■ Technical Details

Size	11.3 x 6.0 x 3.2 cm
Weight	179g
Working Temperature	-20 to +50 °C
Working Humidity	0% - 95% RH (non-condensing)
Ingress Protection	IP66, IP68
Alarms and Type	Visual, vibrating, audible (95 dB) • Low, High, TWA, STEL, OL (over limit)
Tests	Audible/visual alarms on activation; sensors, battery and circuitry (continuous)
Typical Battery Life	18 hours; recharges in less than 6 hours (Note: Approximately 20% capacity loss is normal with lithium polymer batteries after 500 charge cycles. Refer to the Operator's Manual for additional information.)
Warranty	Full three-year warranty including all sensors
Expected Service Lifetime	Five years including all sensors* *Note: Sensors do not contain consumable components and will typically reach the expected lifetime if used according to the instructions in the user manual. Please note that poisoned sensors are not covered by warranty.

### SafetyQuip Gas Detector Servicing

SafetyQuip operates service centres for the Honeywell brand of portable gas detection equipment at many locations around Australia. SafetyQuip service technicians are available to attend client premises in many metro and regional areas for on-site service assistance.

Service technicians are trained and accredited by the equipment manufacturer to diagnose faults and conduct scheduled service work, in addition to supporting client personnel in the safe operation of gas detection equipment.

