

# TACTICIAN RIGGERS HARNESS

PART CODE: **H201**



**HEIGHT  
SAFETY**

## PRODUCT FEATURES >

- Pebble Weave Webbing design provides maximum grip for buckles, eliminating webbing slippage and the need for continual re-adjustment.
- High Tenacity UV stabilised webbing, enhances resistance to solvents and UV light degradation.
- Retro-Reflective Thread in webbing for improved visibility in low light.
- Rear Barr D allows easier access and better weight distribution for twin retractable fall arrest devices.
- Closed Loop Webbing system on rear Dorsal D maintains positioning of Dorsal D in the event of a fall. Significantly reducing the risk of injury from hardware hitting the back of workers head.
- Extended Belay Loops make connection of hardware easier, also maintains absolute front and centre positioning.
- Sub Pelvic Strap integration along the line of Belay Loops, places the worker away from hardware in the event of a fall, significantly reducing the risk of injury from hardware hitting the worker.
- Comes with Suspension Trauma Strap: One-piece Webbing with a quick connection buckle for faster deployment and connection in the event of a fall.
- Articulated Chest Strap and shoulder adjustment points, designed for additional user comfort and female users, due to lower positioning of strap.
- Confined Space Rescue Loops.
- Tangle free Triangle Back Mesh.
- Padding under buckles.
- Service Pouch on back.



## APPLICATIONS >

Fall Arrest, Construction, Ladder, Scaffolding, Warehouse, Confined Space.

## STANDARDS >



AS/NZS 1891.1:2020  
BMP 713822  
BMP 713823  
Australian Standard



LINQ  
TEST  
LAB  
FACILITY

Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.

Available from



FROM  
**PARAMOUNT  
SAFETY PRODUCTS**



# TACTICIAN RIGGERS HARNESS

PART CODE: **H201**



**HEIGHT  
SAFETY**

## PRODUCT DETAILS >

- AUS/NZ designed and engineered
- Size ranges available - Small, Standard (M-L) and Maxi (XL-2XL)
- 10-year life span from date of manufacture



**REAR  
BARR  
D RING**



**SLOTTED  
PASS  
THROUGH  
BUCKLES**



**FRONT FALL  
ARREST  
ATTACHMENT  
POINTS**



**ATTACHED  
SUSPENSION  
TRAUMA  
STRAP**



**CONFINED  
SPACE  
SPREADER  
BAR  
ATTACHMENT  
POINTS**



**PADDING  
UNDER  
BUCKLES**



## TECHNICAL INFORMATION >

- **Webbing Material:** Polyester; 45mm; UV Resilient
- **Fall Arrest Hardware:** Drop Forged corrosion resistant electrophoresis; high tensile steel
- **Thread:** Polyester; 9.81 Newtons (10kg) extension at break 19.5%
- **Stitch Pattern:** THETA Pattern combines 313 stitches to exceed 28kN of strength; AS/NZ compliant colour contrast
- **Plastic Material:** UV stabilised high-density polyethylene
- **Weight:** 1.6kg
- **Web Tenacity:** 28kN
- **Buckle Strength:** 12 to 17kN. Laser etched or hard marked on buckle
- **Padding Material:** Neoprene laminate



Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.

Available from

