## SILEX+

## THE MODEL WITHOUT COMPROMISE, IN PLATINUM® VERSION

No compromise on performance, comfort, style and affordability, now with Platinum® anti-scratch/anti-fog coating providing maximum protection and performance that exceeds expectations.



- **+** ULTRA-WRAPAROUND FRAME
- **+** ♦ ⊃ L \ T I N L M (+**¬**) SCRATCH AND FOG RESISTANT COATING
- **+** PC/TPR CO-INJECTED TEMPLES FOR GREATER COMFORT
- **+** PANORAMIC FIELD OF VISION
- + FLEX 160° TEMPLES



# SILEX+

### THE MODEL WITHOUT COMPROMISE, IN PLATINUM® VERSION

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
SILEX+	Clear	SILEXPPSI	\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	AS/NZS 1337.1:2010	Anti-scratch/Anti-fog/+>
	Smoke	SILEXPPSF	\(\begin{aligned} \begin{aligned} alig	AS/NZS 1337.1:2010	Anti-scratch/Anti-fog/+>
	<b>6</b> CSP	SILEXPCSP	<b>☆</b> I1 & <b>→</b>	AS/NZS 1337.1:2010	Anti-scratch/Anti-fog/+→
	Strap only (optional)	UNIVSTRAP	-	-	-

#### LENS MARKING

- \*P. Platinum is a permanent coating applied on both sides of the lens that gives a high resistance to scratching (1.4 cd / m²) and to the most aggressive chemicals and delays the onset of fogging for two minutes, as per the testing requirements of EN166.
- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' signifies that the product has been approved for the use both outdoors and indoors, and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear lenses.

#### Ocular lens category:

- O. Range of luminous transmittance 80-100% (Clear)
- 1. Range of luminous transmittance 43-88% (CSP).
- 3. Range of luminous transmittance 8-18% (Smoke)

#### Others symbols:

Manufacturer name

#### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

#### **LENSES**

- 2.2mm polycarbonate
- 9 base curve
- Platinum coating on both side of clear, smoke and CSP lenses
- 99.9% UV 385 Clear
- 99.9% UV 400 Smoke, Twilight and CSP

#### FRAME MARKING

**AS/NZS 1337.1:2010** Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6 mm ball at 45 m/s.

#### **TECHNOLOGIES**



This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments. CSP is also combined with the exclusive PLATINUM® coating that sustainably combats fogging.

#### FLEX 160°

Soft and ultra pliable, 160° FLEX frames can be used to adjust the space between the temples for better wearer comfort.

#### ♦PLATINUM

The new exclusive scratch and fog resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and effectively delays the appearance of fogging.

PACKAGING AND GTIN							
	SILEXPPSI	SILEXPPSF	SILEXPCSP	UNIVSTRAP			
Individual plastic bag	9318330048489	9318330048496	9318330048502	9318330040865			
10 safety spectacles per inner box	(01)19318330048486	(01)19318330048493	(01)19318330048509	-			
240 safety spectacles per outer pack	(01)29318330048483	(01)29318330048490	(01)29318330048506	-			

CHARACTERISTICS				
LENSES	PC - 2,2 mm - Curve 9			
FRAME	-			
TEMPLES	PC + TPR			
STRAP	Nylon/15mm/Adjustable			
SPARE LENSES	No			











Non-contractual pictures

17/03/2020

Available from



