

3M[™] SecureFit[™] Protective Eyewear Series

Technical Data Sheet



3M™ SecureFit™ Protective Eyewear Series comes with a variety of features, because having options in protective eyewear can be critical. Workers can choose from several lenses coating options, including 3M™ Anti-fog, and features like a removable foam gasket that combines with Pressure Diffusion Temple (PDT) Technology to create a secure and comfortable fit.

Internal testing per EN168 test method when compared with traditional anti-fog coatings.

Applications

The range covers a variety of hazards and specific tasks. These products can be used in a wide range of applications including Painting, Plastering and other forms of DIY, Foundry work, Engineering, General assembly, Woodworking and Construction.

Standards

3M[™] SecureFit[™] Protective Eyewear Series have been tested and certified to AS/NZS 1337.1:2010 and have a medium impact (I) rating.

Maintenance/cleaning

If the lens becomes scratched or pitted it should be replaced. Avoid exposure or contact of the lens with vapour or liquids which may cause surface crazing and reduce the impact resistance. Inspect and clean the spectacles regularly and replace if broken or damaged.

Thoroughly clean all surfaces with lens cleaner or mild soap solution. Do not clean spectacle with solvents. Air dry or pat dry with clean, soft cloth or tissue. The use of solvents, harsh detergents or abrasives is not recommended. Avoid exposure to MEK, Sulphuric Acid, Methylene Chloride, Toluene, Paint Thinner & Acetone.

Disposal

As the 3M[™] SecureFit[™] Protective Eyewear Series and their components are subject to dirt, dusts and liquids, etc, they cannot be recycled. If the product is to be disposed of, it should be disassembled and disposed of as solid waste. Please see local authority regulations for disposal advice and locations.



Specifications

| | SecureFit [™] Protective Eyewear Series |
|---------------|---|
| Frame | Polycarbonate |
| Side Arms | Polycarbonate, padded touch points |
| Weight | 21g |
| Lens Material | Polycarbonate |
| Lens Types | Clear Grey Amber Indoor/Outdoor |
| Ratings | Medium Impact |

Lens Markings

Markings on eye protectors are a requirement for certification. It assists users in identifying their intended use. They are identified by the following:

| Standard | Lens Marking | Explanations |
|--------------------|---|---|
| AS/NZS 1337.1:2010 | I = Medium Impact O = Outdoor/Indoor (untinted or amber) | OUTDOOR UNTINTED (FOR INDOOR AND OUTDOOR USE) These protectors are intended for indoor and outdoor use where no optical radiation hazards exist other than solar radiation. |
| | I = Medium Impact (outdoor tinted, smoke, brown or photo chromatic) | OUTDOOR TINTED These protectors are intended for outdoor use where no optical radiation hazards exist other than solar radiation. They are intended to provide adequate protection against sun glare and ultraviolet radiation from the sun. |

Impact protection is determined by the test velocity of a steel ball projectile. A ballistic test rig fires either a 6.00mm or a 6.35mm projectile ball at speeds from 12m, up to 190m per second.

| projection but at apacita from i=in, up to form per decentar | | | | |
|--|-------------------|---|---|--|
| Standard | Rating | Impact Protection Situations | Type of Protection | |
| AS/NZS 1336:2014 | Low Impact | Hammering, handling wire, brick chipping by hand | Spectacles | |
| AS/NZS 1336:2014 | Medium Impact | Grinding, machining metals, woodworking | Spectacles, Eyeshields or lightweight visor systems | |
| AS/NZS 1336:2014 | High Impact | Concrete cutting, high speed disc grinding, metal cutting | Visor systems only | |
| AS/NZS 1336:2014 | Extra High Impact | Abrasive shot blasting, ballistic, military, electrical maintenance | Visor systems only | |

Australian/New Zealand Standards AS/NZS 1336:2014 is an excellent reference document and provides assistance.

Medium impact safety spectacles provide protection from medium energy flying particles. For more information on tinted lenses and compliance testing to AS/NZS 1067 (sunglass standard) contact 3M.

Ordering Information

| 3M Code | Model # | Description |
|-------------|-------------|---|
| AT019494601 | SF101AF-BLK | Polycarbonate Clear Anti-Fog-Anti-Scratch Lens |
| AT019494619 | SF101AS-BLK | Polycarbonate Clear Anti-Scratch Lens |
| AT019494627 | SF102AF-BLK | Polycarbonate Grey Anti-Fog-Anti-Scratch Lens |
| AT019494635 | SF103AF-BLK | Polycarbonate Amber Anti-Fog-Anti-Scratch Lens |
| AT019494643 | SF107AF-BLK | Polycarbonate Indoor Outdoor Grey Anti-Fog- Anti-Scratch Lens |
| 70071676269 | SF201AF-AS | Polycarbonate. Clear Lens |
| 70071695509 | SF202AF-AS | Polycarbonate. Grey Lens |
| 70071676368 | SF401AF-AS | Polycarbonate. Clear Lens |
| 70071695426 | SF402AF-AS | Polycarbonate. Grey Lens |
| 70071695434 | SF410AS-AS | Polycarbonate Indoor/ Outdoor Mirror Lens |
| 70071675345 | SF-FOAM | SecureFit [™] Foam Gasket |

| AT019494437 | SF501AF-BLK | Polycarbonate Clear Anti-Fog-Anti-Scratch Lens |
|-------------|---------------|--|
| AT019494445 | SF501SGAF-BLK | Scotchgard™ Polycarbonate Clear Lens |
| AT019494478 | SF502SGAF-BLK | Scotchgard [™] Polycarbonate Grey Lens |
| AT019494494 | SF503SGAF-BLK | Scotchgard [™] Polycarbonate Amber Lens |
| AT019494528 | SF507SGAF-BLK | Scotchgard [™] Polycarbonate Indoor Outdoor Grey Lens |

Important Notice

To the extent permitted by law, 3M shall not be liable for any loss or damage including any loss of business, loss of profits, or for any indirect, special, incidental or consequential loss or damage arising from reliance upon any information herein provided by 3M. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.



