

RUSH+ SEAL

RUSH+ Seal continues the extension of the popular RUSH+ model. RUSH+ Seal comes assembled with a gasket & strap for excellent dust protection.



1662301FB • Clear Lens



1662302FB • Smoke Lens



1662310PS • Twilight Lens



34 g

+ PLATINUM COATING (P)

+ ADJUSTABLE PVC NOSE BRIDGE PLUS

**CO-MOULDED TEMPLE ARMS FOR SUPERIOR
COMFORT AND GRIP**







**+ 'POSITIVE SEAL' GASKET AND STRAP KIT TO
MAXIMISE PROTECTION IN DUSTY ENVIRONMENTS**

+ ULTRA LIGHT WEIGHT


+ BUILT IN BROW PROTECTION

bollé
SAFETY

RUSH+ SEAL

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
RUSH+ SEAL	 Clear	1662301FB	IO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/Platinum 
	 Smoke	1662302FB	I3	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/Platinum 
	 Twilight	1662310FB	I1	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog/Platinum 

LENS MARKING

 Platinum is permanent coating on both sides of the lens gives them a high resistance to scratching (1.4 cd / m²), to the most aggressive chemicals and delays the onset of fogging for 2 minutes, as per the testing requirements of EN166.

I. The letter 'I' signifies 'Medium Impact' approval.

O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

OCULAR LENS CATEGORY:

- O.** Range of luminous transmittance 80-100% (clear).
- 1.** Range of luminous transmittance 43 -88% (twilight).
- 3.** Range of luminous transmittance 8 -18% (smoke).

APPLICATIONS

- Assembly and production work
- Process work
- Emergency response
- Driving
- Solar UV exposure
- Laboratory


MAIN MARKETS

- Manufacturing
- Medical and dental
- Petrochemical
- Food industry
- Construction
- Government
- Mining

LENSES

- 2mm polycarbonate
- 9 base curve
- Platinum coating on both sides of Clear, Smoke and Twilight lenses
- 100% UV 385 – Clear
- 100% UV 400 – Smoke, ESP & Twilight

CLEANING AND STORAGE

CLEANING : Bollé Safety recommends only using our  **clean** Lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS	
LENSES	PC - 2,2 mm - Curve 9
FRAME	PC
TEMPLES	PC + TPR
STRAP	Non Applicable
FOAM	Yes
SPARE LENSES	No

FRAME MARKING

AS/NZS 1337.1.2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact protection. Resists a 6mm at 45 m/s.

Meets the requirements of splash approval when used with the supplied head strap correctly adjusted.

Available from



bollé
SAFETY