

## TENCATE TECASAFE® PLUS 580 TAPED 2 TONE HI VIS L/W FR NON VENTED ENGINEERED COVERALL

### BC8186T



#### Features

- Sto-nor 9801 FR Reflective tape 'Hoop' pattern around body, lower legs and upper sleeves
- Stand collar
- Concealed plastic press snap front closure
- Two way radio loop or gas monitor loop on both of shoulders
- Front side pockets and follow through pocket to body
- Front chest pockets plastic press studs flap closure
- RHS chest pocket with additional mobile phone pocket
- Full gusset sleeve cuff with plastic press snap closure
- Diamond shape crotch gusset
- LHS cargo pocket with ruler pocket and plastic press snap flap closure
- Front knee darts and contoured back knee seam line
- 10 Multifunctional pockets

#### Fabric

- TenCate Tecasafe® Plus 580 FR Modacrylic/Lyocell/Aramid 197gsm

#### Arc Thermal Protection Value

- ATPV 6.5

#### Personal Protective Equipment Category

- PPE 1

#### Size

- Reg: 77R-117R
- Stout: 92S-132S

Orange/Navy  
(TT02)



TENCATE  
Tecasafe® Plus

BC8186T

## AUSTRALIAN & INTERNATIONAL STANDARDS

### ALL BISLEY GARMENTS COMPLY WITH CARE LABELLING STANDARDS:

- **AS/NZS 2621:1998:** Textiles - Guide to the Selection of Correct Care Labelling Instructions from AS/NZS 1957
- **AS/NZS 1957:1998:** Textiles - Care Labelling
- **AS/NZS 2622:1996:** Textile Products - Fibre Content Labelling

### Australian/ New Zealand Standards

#### AS/NZS 4399:1996: SUN PROTECTIVE CLOTHING - EVALUATION AND CLASSIFICATION

This garment has a sun protection rating of UPF 50+ for all colours

#### AS/NZS 4602.1:2011: HI VISIBILITY SAFETY GARMENTS. GARMENTS FOR HIGH RISK APPLICATION

- This garment is classified as Class D/N under section 8 of this standard. *Class D/N garments are intended to provide wearer with high visibility under daylight viewing and night-time viewing using retro-reflected light. In addition garment designed for night use retro-reflective tape at legs.*

#### AS/NZS 1906.4:2010: HI VISIBILITY MATERIAL FOR SAFETY GARMENTS

- *This garment meets the fluorescent capabilities and the chromaticity reading to ensure that the bright colours are within the required colour range. Retro-reflective tape on this garment also meets the higher retro-reflective performance required.*

### International Standards

#### NFPA70E: ELECTRICAL SAFETY IN THE WORKPLACE

- ASTM F1959 / F1959M - 14 Arc Rating results of ATPV 6.5 cal/cm<sup>2</sup> PPE 1
- ASTM F1506\_15

#### NFPA2112: FLAME RESISTANT GARMENTS FOR PROTECTION OF INDUSTRIAL PERSONNEL AGAINST FLASH FIRE

- ASTM F1930:2015 Flash Fire Exposure (% body burn [2 cal/cm / sec] @ 3 sec) \_ PASS
- ASTM D6413 / D6413M - 15 Vertical Flame Test

#### ISO 11612: PROTECTIVE CLOTHING AGAINST HEAT AND FLAME

- ISO 15025:2000 - Flame Spread [Face and Edge ignition]\_ No hole formation. No Molten or flaming debris. No after flame.

## OVERALLS

## MENS

Sizes <b>REGULAR</b>	<b>77R</b>	<b>82R</b>	<b>87R</b>	<b>92R</b>	<b>97R</b>	<b>102R</b>	<b>107R</b>	<b>112R</b>	<b>117R</b>			
To fit chest size (cm)	87	92	97	102	107	112	117	122	127			
To fit chest size (inches)	34	36	38	40	42	44	46	48	50			
To fit waist size (cm)	77	82	87	92	97	102	107	112	117			
To fit waist size (inches)	30	32	34	36	38	40	42	44	46			
In-leg length (cm)	80	80	82	82	84	84	86	86	87			
<b>Imperial/NZ size</b>	<b>3R</b>	<b>4R</b>	<b>5R</b>	<b>6R</b>	<b>7R</b>	<b>8R</b>	<b>9R</b>	<b>10R</b>	<b>11R</b>			
Sizes <b>STOUT</b>			<b>87S</b>	<b>92S</b>	<b>97S</b>	<b>102S</b>	<b>107S</b>	<b>112S</b>	<b>117S</b>	<b>122S</b>	<b>127S</b>	<b>132S</b>
To fit chest size (cm)			97	102	107	112	117	122	127	132	137	142
To fit chest size (inches)			38	40	42	44	46	48	50	52	54	56
To fit waist size (cm)			87	92	97	102	107	112	117	122	127	132
To fit waist size (inches)			34	36	38	40	42	44	46	48	50	42
In-leg length (cm)			78	78	80	80	82	82	83	83	83	83
<b>Imperial Size</b>			<b>3.25S</b>	<b>4.25S</b>	<b>5.25S</b>	<b>6.25S</b>	<b>7.25S</b>	<b>8.25S</b>	<b>9.25S</b>	<b>10.25S</b>	<b>11.25S</b>	<b>12.25S</b>
NZ size			5S	6S	7S	8S	9S	10S	11S	12S	13S	14S